

MATERIAL SAFETY DATA SHEET

Sodium Chromate Test Solutin "B"

SECTION 1 . Product and Company Identification

Product Name and Synonym: Sodium Chromate Test Solutin "B"
Product Code: 145-402
Material Uses:
Manufacturer: OFI Testing Equipment, Inc.
11302 Steeplecrest Drive
Houston, TX 77065 USA
Phone: (713) 880-9885
Fax: (713) 880-9886
Entry Date : 5/5/2010
Print Date: 7/28/2010
24 Hour Emergency Assistance : Chemtrec 800-424-9300
Canutec 613-996-6666

Health:	3			
Flammability:	0			
Reactivity:	0			
Hazard Rating:				
Least	Slight	Moderate	High	Extreme
0	1	2	3	4
NA = Not Applicable		NE = Not Established		

SECTION 2 HAZARD IDENTIFICATION

Causes severe irritation and burns. May Be harmful if swallowed. Avoid breathing vapor or dust. Use with adequate ventilation. Avoid contact with eyes, skin, and clothes. Wash thoroughly after handling. Keep container closed.

Emergency Overview: Danger! Corrosive. Liquid And Mist Cause Severe Burns To All Body Tissue. May Be Fatal If Swallowed Or Inhaled.

Inhalation: Corrosive! Inhalation of Vapors can cause Coughing, Choking, Inflammation, of the Nose, Throat, and Upper Respiratory Tract, and in Severe Cases, Pulmonary Edema, Circulatory Failure, and Death.

Ingestion: Corrosive! Swallowing Hydrochloric Acid can cause Immediate Pain and Burns of the Mouth, Throat, Esophagus, and Gastrointestinal Tract. May cause Nausea, Vomiting, and Diarrhea, and in Severe Cases, Death.

Skin: Corrosive! Can cause Redness, Pain, and Severe Skin Burns. Concentrated Solutions Cause Deep Ulcers and Discolor of Skin.

Eye Contact: Corrosive! Vapors are Irritating and May cause Damage to Eyes. Contact May cause Severe Burns and Permanent Eye Damage.

Chronic Exposure: Long-Term Exposure to Concentrated Vapors May cause Erosion of Teeth. Long-Term Exposures Seldom Occur due to the Corrosive Properties of the Acid.

Aggravated by Exposure: Persons with Pre-Existing skin Disorders or Eye Disease May be more Susceptible to the Effects of this Substance.

SECTION 3 MIXTURE COMPONENTS

SARA 313	Component	CAS Number	Percent Comp.	Dimension	Exposure Limits
<input checked="" type="checkbox"/>	Hydrochloric Acid	CAS# 7647-01-0	50%	V/V	OSHA PEL (C) 5 ppm, (C) 7 mg/m ³
<input type="checkbox"/>	Water, Deionized ASTM Type II	CAS# 7732-18-5	50%	V/V	None Established

Sodium Chromate Test Solutin "B"

SECTION 4 FIRST AID MEASURES

Causes severe irritation and burns. May Be harmful if swallowed. Avoid breathing vapor or dust. Use with adequate ventilation. Avoid contact with eyes, skin, and clothes. Wash thoroughly after handling. Keep container closed.

FIRST AID: CALL A PHYSICIAN. SKIN: In case of contact, immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Thoroughly clean clothing and shoes before reuse.

EYES: Wash eyes with plenty of water for at least 15 minutes, lifting lids occasionally. Seek Medical Aid. INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen

INGESTION: Give several glasses of milk or water. Vomiting may occur spontaneously, but DO NOT INDUCE! Never give anything by mouth to an unconscious person.

SECTION 5 FIRE FIGHTING MEASURES

Fire Extinguisher Type: Any means suitable for extinguishing surrounding fire

Fire / Explosion Hazards: None

Fire Fighting Procedure: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and clothing.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Absorb spill with inert material, then place in a chemical waste container. Neutralize with a weak base.

Ventilate area of Leak or Spill. Wear Appropriate Personal Protective Equipment as Specified in Section 7. Isolate Hazard Area. Keep Unnecessary and Unprotected Personnel from Entering.

Contain and Recover Liquid when Possible. Neutralize with Alkaline Material (Soda-Ash, Lime), then Absorb with an Inert Material (e.g., Vermiculite, Dry Sand, Earth), and place in a Chemical Waste Container. Do Not Use Combustible Materials, such as Saw Dust.

SECTION 7 HANDLING AND STORAGE

Store in a cool dry place. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection: NIOSH/MSHA-approved respirator

Ventilation

Local Exhaust

Mechanical

Protective Gloves: Wear appropriate gloves to prevent skin exposure

Eye Protection: Goggles and Face Shield

Other Protective Equipment: Wear appropriate clothing to prevent skin exposure

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Melting Point: Information not available Percent Volatile by Volume: > 99

Sodium Chromate Test Solutin "B"

Boiling Point:	Information not available	Evaporation Rate	Information not available
Vapor Pressure:	Information not available	Evaporation Standard	
Vapor Density:	Information not available	Auto Ignition Temp	Not applicable
Solubility in Water:	Soluble	Lower Flamm. Limit in Air	Not applicable
Appearance /Odors:	Clear colorless solution/slight HCL odor	Upper Flamm. Limit in Air	Not applicable
Flash Point:	Not flammable		
Specific Gravity:	Information not available		

SECTION 10 STABILITY AND REACTIVITY INFORMATION

Stability:	Stable
Conditions to Avoid:	None known
Materials to Avoid:	Oxidizing agents, metals, bases.
Hazardous Decomposition Products:	HCl fumes, Chlorine
Hazardous polymerization:	Will Not Occur
Conditions to Avoid:	None known

SECTION 11 Toxicological Information

Hydrogen Chloride - IARC Category 3, NTP Carcinogen - Known: No

SECTION 12 Ecological Information

When Released into the Soil, this Material is Not Expected to Biodegrade. When Released into the Soil, this Material may Leach into Groundwater.

SECTION 13 Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14 Transport Information

DOT Classification: Hydrochloric Acid Solution, 8, UN1789, PG II

DOT Regulations may change from time to time. Please consult the most recent D.O.T. regulations.

SECTION 15 Regulatory Information

Chemical Inventory Status –
Part 1:Ingredient
Hydrogen Chloride (7647-01-0)
Water (7732-18-5)
TSCA Yes
EC Yes
Japan Yes
Australia Yes

Sodium Chromate Test Solutin "B"

Chemical Inventory Status –
Part 2:Ingredient
Hydrogen Chloride (7647-01-0)
Water (7732-18-5)
Korea Yes
DSL Yes
NDSL No
Phil. Yes

Federal, State & International Regulations –
Part 1: Ingredient.
Hydrogen Chloride (7647-01-0)
Water (7732-18-5)
RQ 5000
TPQ 500*
List Yes
Chemical Catg No

Federal, State &
International Regulations –
Part 2:Ingredient
Hydrogen Chloride (7647-01-0)
Water (7732-18-5)
CERCLA 5000
261.33 No
8(d) No

Chemical Weapons Convention:No

TSCA 12 (b):No

CDTA:No
Mixture/Liquid)


SARA 311/312: Acute: Yes
Chronic: Yes
Fire: Yes
Pressure: No
Reactivity: No

SECTION 16

Additional Information

Corrosive! Conditions aggravated/Target organs: Persons with preexisting skin, eye, or respiratory disorders may be more susceptible. Acute: Severe irritation or burns to skin, eyes, lungs, mucous membranes, and GI tract. May be fatal by pulmonary edema or gastric necrosis. Chronic: Dermatitis, eye damage, erosion & discoloration of teeth.

Sodium Chromate Test Solutin "B"



Revisions

	NFPA	
	0	
7/27/2010	0.1	updated msds to 16 section from 10 section msds. STN

The information herein is believed to be accurate and is offered in good faith for the user's consideration and investigation. No warranty either expressed or implied is made for the completeness or accuracy of the information whether originating from the above mentioned company or not. Users of this material should satisfy themselves by independent investigation of current scientific and medical knowledge that the material can be used safely.