Printing date 01/15/2018

Reviewed on 01/15/2018

 $(Contd. \ on \ page \ 2)$

- US -

nting date 01/15/2018	Reviewed on 01/15/2
Identification	
Product identifier	
Trade name: Xylene, Technical Grade	
Article number: 280-20	
CAS Number:	
1330-20-7	
EC number: 215-535-7	
Index number:	
601-022-00-9	
Details of the supplier of the safety data sheet	
Manufacturer/Supplier:	
OFI Testing Equipment Inc. 11302 Steeplecrest Dr.	
Houston, TX 77065	
(877) 837-8683	
Information department: techservices@ofite.com	
Emergency telephone number:	
INFOTRAC USA - CANADA: 1-800-535-5053 INTERNATIONAL: 1-352-323-3500	
Classification of the substance or mixture	
GHS02 Flame	
\bigtriangledown	
Flam. Liq. 3 H226 Flammable liquid and vapor.	
\wedge	
GHS07	
Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled.	
Skin Irrit. 2 H315 Causes skin irritation.	
Label elements	
• GHS label elements The substance is classified and labeled according to the	he Globally Harmonized System (Gl
Hazard pictograms	
\land	
GHS02 GHS07	
• Signal word Warning	
Hazard statements	
Flammable liquid and vapor. Harmful in contact with skin or if inhaled.	
Causes skin irritation.	
Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Keep container tightly closed.	(Contd. on pa

Printing date 01/15/2018

Reviewed on 01/15/2018

Trade name: Xylene, Technical Grade

	(Contd. of page 1)
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
If skin irritation occurs: Get medical advice/attention.	
Take off contaminated clothing and wash it before reuse.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep cool.	
Dispose of contents/container in accordance with local/regional/national/international regulation	5.
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 2	
Fire = 3	
$\frac{2}{10} Reactivity = 0$	
· HMIS-ratings (scale 0 - 4)	
HEALTH 2 $Health = 2$	
FIRE 3 Fire = 3	
REACTIVITY 0 <i>Reactivity</i> = 0	
· Other hazards	
· Results of PBT and vPvB assessment	
• PBT: Not applicable.	
• vPvB : Not applicable.	
3 Composition/information on ingredients	
· Chemical characterization: Substances	

- CAS No. Description
- 1330-20-7 Xylene (Xylol) • Identification number(s)
- *EC number*: 215-535-7
- Index number: 601-022-00-9

4 First-aid measures

- \cdot Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Printing date 01/15/2018

Reviewed on 01/15/2018

(Contd. of page 2)

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:

Trade name: Xylene, Technical Grade

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 *Fire-fighting measures*

- Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

US

Printing date 01/15/2018

Reviewed on 01/15/2018

Trade name: Xylene, Technical Grade

(Contd. of page 3)

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 1330-20-7 Xylene (Xylol)

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm

· Ingredients with biological limit values:

CAS: 1330-20-7 Xylene (Xylol)

- BEI 1.5 g/g creatinine
 - LD50 Intraperitoneal: urine Time: end of shift LD50: Methylhippuric acids

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

• Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 5)

Printing date 01/15/2018

Reviewed on 01/15/2018

Trade name: Xylene, Technical Grade

(Contd. of page 4)

Physical and chemical proper	ties
Information on basic physical and	chemical properties
· General Information	
· Appearance:	
Form:	Liquid
Color:	Colorless
· Odor:	Solvent-like
• Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Information not °C
Boiling point/Boiling range:	Information not °C
Flash point:	30 °C (86 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	500 °C (932 °F)
• Decomposition temperature:	Not determined.
• Auto igniting:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
• Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
Vapor pressure at 20 °C (68 °F):	6.7-8.2 hPa (5-6.2 mm Hg)
Density at 20 °C (68 °F):	0.87 g/cm ³ (7.26015 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
• Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water at 20 °C (68 °F):	0.2 g/l
· Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	0.61 mPas
Kinematic:	Not determined.
Other information	No further relevant information available.

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

(Contd. on page 6)

US

Printing date 01/15/2018

Reviewed on 01/15/2018

(Contd. of page 5)

Trade name: Xylene, Technical Grade

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer) 3

- · NTP (National Toxicology Program) Substance is not listed.
- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Assessment by list): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- \cdot Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 7)

Printing date 01/15/2018

Reviewed on 01/15/2018

Trade name: Xylene, Technical Grade

(Contd. of page 6)

TINI NI	
UN-Number DOT, IMDG, IATA	UN1307
UN proper shipping name	
DOT	Xylenes
IMDG, IATA	XYLENES
Transport hazard class(es)	
DOT	
RAMMBEE LOUD	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
3 Class Label	3 Flammable liquids 3
Packing group DOT, IMDG, IATA	III
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	30
EMS Number:	F-E,S-D
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1307 XYLENES, 3, III

(Contd. on page 8)

Printing date 01/15/2018

Reviewed on 01/15/2018

Trade name: Xylene, Technical Grade

(Contd. of page 7)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture • Sara
- · Section 355 (extremely hazardous substances): Substance is not listed. · Section 313 (Specific toxic chemical listings): Substance is listed.
- TSCA (Toxic Substances Control Act):

Xylene (Xylol)

· Proposition 65

- · Chemicals known to cause cancer: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is not listed.

- · EPA (Environmental Protection Agency) I
- TLV (Threshold Limit Value established by ACGIH) A4
- · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.
- GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Warning · Hazard statements Flammable liquid and vapor. Harmful in contact with skin or if inhaled. Causes skin irritation. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 9)

[·] Carcinogenic categories

Printing date 01/15/2018

Reviewed on 01/15/2018

Trade name: Xylene, Technical Grade

(Contd. of page 8)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

· Date of preparation / last revision
01-15-2018: review SDS for accuracy. STN
Creation date for SDS 03-25-2014. STN
Revision 0.1, 05-07-2015: corrected emergency and information contacts. STN
01/15/2018 / -
• Abbreviations and acronyms:
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International
Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
US